

SERIE M - MINI VALVOLA A SFERA M SERIES - MINI BALL VALVE



DESCRIZIONE / DESCRIPTION

Mini valvola a sfera con comando manuale ON/OFF con maniglietta.

Mini ball valve with manual command ON/OFF with handle.

FUNZIONAMENTO / FUNCTION

Si chiude e si apre girando la maniglietta da $\frac{1}{4}$ di giro fino a fine corsa.

Open and close by turning the handle of $\frac{1}{4}$ turn, till the end of the stroke.

DIREZIONE DI FLUSSO / DIRECTION OF THE FLOW

Libero a scelta.
Free.

IMPIEGO / USE

Aria compressa – Aria compressa lubrificata – Gas vari – Liquidi in genere.

Compressed air – Lubrificated compressed air – Various gasses – Various liquids.

PRESSIONE DI ESERCIZIO / WORKING PRESSURE

20 bar (2 MPa)

TEMPERATURA DI ESERCIZIO / WORKING TEMPERATURE

- 5 °C + 70 °C (+ 23 °F + 160 °F)

MATERIALI / MATERIALS

Corpo / Body : Ottone CW617N / Brass

Manicotto / Sleeve : Ottone CW614N / Brass

Alberello / Pin : Ottone CW614N / Brass

Sfera / Ball	:	Ottone CW614N / Brass
Seggi / Seats	:	PTFE vergine / Virgin PTFE
Vite / Scren	:	Acciaio / Steel
O-Ring / O-Ring	:	NBR 70 / NBR 70
Maniglietta / Handle	:	Nylon 6-6 / Nylon 6-6
Tappo / Button	:	Nylon 6-6 / Nylon 6-6

FINITURA ESTERNA / FINISH

Nichelata.
Nickel plated.

MISURE / SIZES

1/8" – 1/4" – 3/8" – 1/2"

ESTREMITÀ / EXTREMITY

Con filetti / With threads G / GA – ISO 228 – R ISO7 (Rp – ISO 7 – NPT a richiesta / on request)

FORMA / SHARE

Femmina – Femmina / Female – Female

Maschio – Femmina / Male – Female

Maschio – Maschio / Male – Male

Attacco per tubi in rame e in alluminio con dado e bicono.

Connection for copper tubes / aluminium tubes with nut and ogives.



MVS
CO-SOURCING FOR QUALITY PRODUCTS